

# CECI 120

IN-GROUND



Driver-over in-ground luminaries with no visible screws, made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Round or square shape available with several cover versions. Supplied as standard with TÜV-CB certified, long-life, efficient and **Kelvin settable GX53 LED lamp included**. Insulation class II, Protection rating IP67.



*Apparecchio per incasso a terra carrabile e senza viti a vista, realizzato in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Disponibile con forma quadrata o circolare in diverse versioni di cover. Fornito con inclusa lampadina a LED GX53 con Kelvin impostabile certificata TÜV-CB, di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP67.*



2F1.000.G1K

**CCT SETTABLE**

3000 K 4000 K 6500 K

SDCM <6




**CECI 120 - COMPONENTS**



**IP67**




**COVER** with no visible screws made of shockproof resin material, UV-rays stabilized, rust and corrosion free. Round or square design, 2 or 3 light versions available for a diffuse or directed light emission.



**COVER** senza viti a vista realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Disponibile nelle versioni quadrata o ad anello, a 2 aperture e a 3 aperture per permettere un'emissione della luce diffusa o direzionata.

**DIFFUSER** made of high impact and high-pressure load resistant resin material (PC), complete with silicone rubber gasket to ensure high protection against external agents. Frosted or coloured versions, to get a customized ambiance.

**DIFFUSORE** in resina antiurto altamente resistente al carico (PC), completo di guarnizione in gomma siliconica per garantire un alto livello di protezione contro gli agenti esterni. Disponibile nella versione satinata o colorata, per ottenere un'ambientazione personalizzata.



**HOUSING** made of shockproof resin material, provided with double holes and double watertight cable glands for safe connecting cable.

**CASSA** realizzata in resina antiurto, provvista di doppi fori e doppio pressacavo a tenuta stagna, per consentire in maniera sicura l'ingresso e l'uscita delle connessioni elettriche.

**INSTALLATION HOUSING** made of shockproof resin material to be fixed into the ground before installing the luminaries.

**CONTRO-CASSA** in resina antiurto da fissare al suolo prima dell'installazione degli apparecchi.

**CECI 120**



**Dimensions and weight**  
Installation housing depth: 93 mm  
Diameter: Ø 120 mm  
Weight: 0,45 Kg

**Cover colours:**



**Diffuser PC:**



**LED LAMPS**



Technical details on page 552.

**GX53 LED**

100 - 240 V

\*ADD. SUFFIX



3 W

350 Lm

6500 K

4000 K

3000 K

.G1K

**3W 350 Lm = 40W incandescent**


**SAVE 93%**



In-ground supplied as standard with TÜV-CB certified, long-life, efficient and Kelvin settable GX53 LED lamp included. Quick and easy lamp replacement for a very simple maintenance after installation.

- **COST SAVING:** long-life and efficient LED light sources
- **BUILT-IN DRIVER:** quick and easy lamp replacement
- **GREAT FLEXIBILITY:** GX53 standard lamp holder
- **FUTURE-PROOFED LUMINARIES:** performances easy to upgrade to latest technology developments.

**CCT SETTABLE LED LAMP**



CCT switch settable in three different positions, to select the desired Kelvin temperature (3000K/4000K/6500K) and get a customized ambiance.

\* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE



COMPANY  
UP&DOWN  
DOWNLIGHT  
IN-GROUND  
BRICKLIGHT  
FLOODLIGHT  
BOLLARD  
BULKHEAD  
GARDEN  
URBAN CLASSIC  
URBAN MODERN  
POST  
LAMPS  
REFERENCES

**CECI 120**  
IN-GROUND



2F3.000.AUG1K



2F1.000.G1K



2F4.000.G1K



2F2.000.LUG1K





**CECI 120** 2F1.000.G1K

**3W**

CCT SETTABLE GX53 LED LAMP INCLUDED  
3000K/4000K/6500K

Pcs 36  
Kg 15,7  
mc 0,084

**CECI 120-3L** 2F3.000.G1K

**3W**

CCT SETTABLE GX53 LED LAMP INCLUDED  
3000K/4000K/6500K

Pcs 36  
Kg 15,7  
mc 0,084

**CECI 120-2L** 2F2.000.G1K

**3W**

CCT SETTABLE GX53 LED LAMP INCLUDED  
3000K/4000K/6500K

Pcs 36  
Kg 15,7  
mc 0,084

**CECI 120-SQ** 2F4.000.G1K

**3W**

CCT SETTABLE GX53 LED LAMP INCLUDED  
3000K/4000K/6500K

Pcs 36  
Kg 15,7  
mc 0,084