

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 713124
Type of light source: LED



Product information Sheet

General Information

Material number	713124
Type	Garden Lamp
Product segment	Outdoor

Dimensions

Length (in cm)	12.5 cm
Width (in cm)	22 cm
Height (in cm)	80 cm
Net Weight	

Material & Colour

Enclosure Material	Aluminium & Acrylic Diffuser
Colour	Dark Grey
Adjustable	

Functionality

Switch Type	
Function	
Battery	
USB Charger	


Technical Information

Protection Degree	IP54
Protection Class	Class I
Mains Voltage	220-240
max. Wattage	2x6W
Lumen	1044lm
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	25000hours
Switching Cycles	30000
Colour Rendering Index (Ra, CRI)	>80
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	MLS
Connected light source (CLS) [yes/no]	NO
Colour-tuneable light source [yes/no]	NO
Envelope [no/second/non-clear]	NO
High luminance light source [yes/no]	NO
Anti-glare shield [yes/no]	NO
Dimmable [yes/only with specific dimmers/no]	NO

General Product parameters

Energy consumption in on-mode (kWh/1000h)	12
Energy efficiency class	F
The calculations performed with the parameters, including the determination of the energy class	F
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	520lm*2
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3000K
On-mode power (P_{on}), expressed in W [x,x]	6*2
Standby power (P_{sb}), expressed in W and rounded to the second decimal	10
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	94*72*10
Networked standby power (P_{net}) in W for connected light sources (CLS)	
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	
Spectral power distribution in the range 250 nm to 800 nm, at full-load	

Claim of equivalent power (c)	
If yes, equivalent power (W)	
Chromaticity coordinates (x and y)	0.400 0.252

Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	
Beam Angle in degrees for directional light source	144.6

Parameters for LED and OLED light sources

R9 colour rendering index value	
Survival factor [x,xx]	1.0
The lumen maintenance factor [x,xx]	95.8%
Displacement factor ($\cos \phi_1$)	0.9
Displacement factor ($\cos \phi_1$) for LED and OLED mains light sources	0.9
Colour consistency in MacAdam ellipses	<6
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	1.3
Flicker metric ($P_{st} Lm$) [x,x]	0.082
Flicker metric ($P_{st} LM$) for LED and OLED light sources	0.069
Stroboscopic effect metric (SVM) [X,X]	2.89
Stroboscopic effect metric (SVM) for LED and OLED light sources	2.853
P_{on} in W	10W

