

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 8105617
Type of light source: LED



Product information Sheet

General Information

Material number	8105617
Type	Ceiling light
Product segment	INDOOR

Dimensions

Diameter (in cm)	41Cm
Width (in cm)	
Height (in cm)	8.5Cm
Height 2 (in cm)	
Cut Out (in cm)	
Net Weight (in cm)	2.1Kg

Material & Colour

Enclosure Material	Metal & Acrylic
Colour	Sandy gray
Adjustable	

Functionality

Switch Type	
Function	Triac dimmable
Battery	No
USB Charger	No

Technical Information

Protection Degree	IP20
Protection Class	
Mains Voltage	
max. Wattage	50W
Lumen	3250
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	75000H
Switching Cycles	
Colour Rendering Index (Ra, CRI)	80
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	6

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	No
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	No

General Product parameters

Energy consumption in on-mode (kWh/1000h)	50
Energy efficiency class	E
The calculations performed with the parameters, including the determination of the energy class	
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1100 in sphere
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3000K
On-mode power (P_{on}), expressed in W [x,x]	9,0W
Standby power (P_{sb}), expressed in W and rounded to the second decimal	
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	556*13*1
Spectral power distribution in the range 250 nm to 800 nm, at full-load	
Claim of equivalent power (c)	
If yes, equivalent power (W)	
Chromaticity coordinates (x and y)	0.440/0.403

Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	
Stanby Power (P_{sb}) in W	
Beam Angle in degrees for directional light source	

Parameters for LED and OLED light sources

R9 colour rendering index value	0
Survival factor [x,xx]	0.9
The lumen maintenance factor [x,xx]	0.96
Displacement factor ($\cos \phi_1$)	
Colour consistency in MacAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage If yes then replacement claim (W)	
Flicker metric ($P_{st} Lm$) [x,x]	
Stroboscopic effect metric (SVM) [X,X]	
Displacement factor ($\cos \phi_1$) for LED and OLED mains light sources LED/OLED	
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	
Flicker metric ($P_{st} LM$) for LED and OLED light sources	
Stroboscopic effect metric (SVM) for LED and OLED light sources	
P_{on} in W	

