

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 8142281
Type of light source: LED



Product information Sheet

General Information

Material number	8142281
Type	Wall lamp
Product segment	INDOOR

Dimensions

Length (in cm)	57Cm
Width (in cm)	4.5Cm
Height (in cm)	19Cm
Height 2 (in cm)	
Cut Out (in cm)	
Net Weight (in cm)	

Material & Colour

Enclosure Material	Aluminium & Acrylic
Colour	Chrome
Adjustable	

Functionality

Switch Type	-
Function	-
Battery	No
USB Charger	No

Technical Information

Protection Degree	IP44
Protection Class	II
Mains Voltage	220V
max. Wattage	12W
Lumen	530
Equivalence With Incandescent Lamp (W)	-
Colour Temperature	3000K
Nominal Lifetime (in h)	20000H
Switching Cycles	>15000
Colour Rendering Index (Ra, CRI)	80
Rated Lamp Power (0,1W precision)	12W
Colour Tolerance (LED, SDCM)	5

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	Yes
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	No
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	Yes
Dimmable [yes/only with specific dimmers/no]	No

General Product parameters

Energy consumption in on-mode (kWh/1000h)	12k
Energy efficiency class	F
The calculations performed with the parameters, including the determination of the energy class	F
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	960
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3000K
On-mode power (P_{on}), expressed in W [x,x]	12W
Standby power (P_{sb}), expressed in W and rounded to the second decimal	0
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	L:45*4.5*19
Spectral power distribution in the range 250 nm to 800 nm, at full-load	
Claim of equivalent power (c)	
If yes, equivalent power (W)	
Chromaticity coordinates (x and y)	

Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	
Standby Power (P_{sb}) in W	0

Parameters for LED and OLED light sources

R9 colour rendering index value	1
Survival factor [x,xx]	1
The lumen maintenance factor [x,xx]	95%
Displacement factor ($\cos \phi_1$)	0,95
Colour consistency in MacAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric ($P_{st Lm}$) [x,x]	0,0035
Stroboscopic effect metric (SVM) [X,X]	0,0015
Displacement factor ($\cos \phi_1$) for LED and OLED mains light sources LED/OLED	0,95
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	5
Flicker metric (P_{stLM}) for LED and OLED light sources	0,0035
Stroboscopic effect metric (SVM) for LED and OLED light sources	0,0015
P_{on} in W	12

