

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A

Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE

Model identifier: 9026002

Type of light source: LED



Product information Sheet

General Information

Material number	9026002
Type	
Product segment	Outdoor

Dimensions

Diameter (in cm)	16 Cm
Width (in cm)	10 Cm
Height (in cm)	16 Cm
Net Weight	

Material & Colour

Enclosure Material	Acrylic Diffuser
Colour	Dark Gray
Adjustable	

Functionality

Switch Type	
Function	
Battery	
USB Charger	

Technical Information

Protection Degree	IP65
Protection Class	
Mains Voltage	220-240V
max. Wattage	12W
Lumen	630Lm
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	25000h
Switching Cycles	N/A
Colour Rendering Index (Ra, CRI)	>80
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	MLS
Connected light source (CLS) [yes/no]	
Colour-tuneable light source [yes/no]	
Envelope [no/second/non-clear]	NON-CLEAR
High luminance light source [yes/no]	YES
Anti-glare shield [yes/no]	
Dimmable [yes/only with specific dimmers/no]	

General Product parameters

Energy consumption in on-mode (kWh/1000h)	12
Energy efficiency class	E
The calculations performed with the parameters, including the determination of the energy class	
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1307
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3000K
On-mode power (P_{on}), expressed in W [x,x]	11.27
Standby power (P_{sb}), expressed in W and rounded to the second decimal	0
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	83.4
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	
Spectral power distribution in the range 250 nm to 800 nm, at full-load	

Claim of equivalent power (c)

If yes, equivalent power (W)

Chromaticity coordinates (x and y)

Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	
Beam Angle in degrees for directional light source	N/A

Parameters for LED and OLED light sources

R9 colour rendering index value	11
Survival factor [x,xx]	0.9
The lumen maintenance factor [x,xx]	0.96
Displacement factor ($\cos \phi_1$)	0.793
Displacement factor ($\cos \phi_1$) for LED and OLED mains light sources	
Colour consistency in MacAdam ellipses	
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	1.5
Flicker metric (Pst Lm) [x,x]	1
Flicker metric (PstLM) for LED and OLED light sources	
Stroboscopic effect metric (SVM) [X,X]	0.4
Stroboscopic effect metric (SVM) for LED and OLED light sources	
P_{on} in W	

