


NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 9060613
Type of light source: LED



Product information Sheet

General Information

| | |
|-----------------|------------|
| Material number | 9060613 |
| Type | Wall light |
| Product segment | INDOOR |

Dimensions

| | |
|----------------|--------|
| Length (in cm) | 60 Cm |
| Width (in cm) | 2.7 Cm |
| Height (in cm) | 7.5 Cm |
| Net Weight | |

Material & Colour

| | |
|--------------------|-------------|
| Enclosure Material | Aluminium |
| Colour | Sandy Black |
| Adjustable | No |

Functionality

| | |
|-------------|-----------------|
| Switch Type | No |
| Function | LED PHILIPS SMD |
| Battery | No |
| USB Charger | No |

Technical Information

| | |
|--|-------------|
| Protection Degree | IP44 |
| Protection Class | |
| Mains Voltage | AC 220-240V |
| max. Wattage | 22W |
| Lumen | 1540Lm |
| Equivalence With Incandescent Lamp (W) | |
| Colour Temperature | 3000K |
| Nominal Lifetime (in h) | 30000H |
| Switching Cycles | - |
| Colour Rendering Index (Ra, CRI) | CRI >90 |
| Rated Lamp Power (0,1W precision) | - |
| Colour Tolerance (LED, SDCM) | |

Product information

| | |
|---|-----|
| Lighting technology used [LED/OLED/MIXED/OTHER] | LED |
| Non-directional or directional [NDLS/DLS] | |
| Mains or non-mains [MLS/NMLS] | |
| Connected light source (CLS) [yes/no] | |
| Colour-tuneable light source [yes/no] | |
| Envelope [no/second/non-clear] | |
| High luminance light source [yes/no] | |
| Anti-glare shield [yes/no] | |
| Dimmable [yes/only with specific dimmers/no] | No |

General Product parameters

| | |
|--|-------|
| Energy consumption in on-mode (kWh/1000h) | 11k |
| Energy efficiency class | F |
| Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | |
| Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set : | 3000K |
| On-mode power (P_{on}), expressed in W [x,x] | |
| Standby power (P_{sb}), expressed in W and rounded to the second decimal | |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | |
| Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set | |
| Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre): | |
| Spectral power distribution in the range 250 nm to 800 nm, at full-load | |

| | |
|------------------------------------|--|
| Claim of equivalent power (c) | |
| If yes, equivalent power (W) | |
| Chromaticity coordinates (x and y) | |

Parameters for directional light sources

| | |
|--|--|
| Peak luminous intensity (cd) | |
| Beam angle in degrees, or the range of beam angles that can be set | |

Parameters for LED and OLED light sources

| | |
|--|-----|
| R9 colour rendering index value | |
| Survival factor [x,xx] | |
| The lumen maintenance factor [x,xx] | 70% |
| Displacement factor ($\cos \phi_1$) | |
| Colour consistency in McAdam ellipses | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage | |
| If yes then replacement claim (W) | |
| Flicker metric ($P_{st} L_m$) [x,x] | |
| Stroboscopic effect metric (SVM) [X,X] | |
| P_{on} in W | |

