NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE Model identifier: 9077881 Type of light source: LED



Product information Sheet

General Information

Material number	9077881
Туре	Pendant
Product segment	INDOOR

Dimensions

Diameter (in cm)	45Cm
Width (in cm)	55Cm
Height 1 Height 2 (in cm)	22Cm 120Cm
Net Weight (in cm)	

Material & Colour

Enclosure Material	Metal & Acrylic Diffuser
Colour	Sandy Black & Sandy White
Adjustable	
Functionality	
Switch Type	
Function	-
Battery	No
USB Charger	No

Technical Information

Protection Degree	IP20
Protection Class	II
Mains Voltage	220V
max. Wattage	30W
Lumen	1680
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	20000H
Switching Cycles	>15000
Colour Rendering Index (Ra, CRI)	80
Rated Lamp Power (0,1W precision)	30W
Colour Tolerance (LED, SDCM)	5

Product information	
Froduct mormation	
Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDL
Mains or non-mains [MLS/NMLS]	NML
Connected light source (CLS) [yes/no]	Yes
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	No
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	Yes
Dimmable [yes/only with specific dimmers/no]	No
General Product parameters	
Energy consumption in on-mode (kWh/1000h)	30W
Energy efficiency class	А
The calculations performed with the parameters, including the determination of the energy class	Α
Useful luminus flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1950lm
Correlated colour temperature, rounded to the nearest 100 K,	192010
or the range of correlated colour temperatures, rounded to the nearest 100 K,	3000K
On-mode power (Pon), expressed in W [x,x]	30W
Standby power (Psb), expressed in W and rounded to the second decimal	0
Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal	
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	D45*H180
Spectral power distri bution in the range 250 nm to 800 nm, at full-load	21011100
Claim of equivalent power (^c)	No
If yes, equivalent power (W)	
Chromaticity coordinates (x and y)	
Parameters for directional light sources	
Parameters for directional light sources Peak luminous intensity (cd)	
Peak luminous intensity (cd)	
Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set	0
Peak luminous intensity (cd)	0
Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set Stanby Power (Psb) in W Beam Angle in degrees for directional light sourrce	0
Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set Stanby Power (Psb) in W Beam Angle in degrees for directional light source Parameters for LED and OLED light sources	
Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set Stanby Power (Psb) in W Beam Angle in degrees for directional light source Parameters for LED and OLED light sources R9 colour rendering index value	1
Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set Stanby Power (Psb) in W Beam Angle in degrees for directional light source Parameters for LED and OLED light sources R9 colour rendering index value Survival factor [x,xx]	1 1
Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set Stanby Power (Psb) in W Beam Angle in degrees for directional light source Parameters for LED and OLED light sources R9 colour rendering index value Survival factor [x,xx] The lumen maintenance factor [x,xx]	1 1 95%
Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set Stanby Power (Psb) in W Beam Angle in degrees for directional light source Parameters for LED and OLED light sources R9 colour rendering index value Survival factor [x,xx] The lumen maintenance factor [x,xx] Displacement factor (cos φ1)	1 1
Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set Stanby Power (Psb) in W Beam Angle in degrees for directional light source Parameters for LED and OLED light sources R9 colour rendering index value Survival factor [x,xx] The lumen maintenance factor [x,xx] Displacement factor (cos φ1) Colour consistency in McAdam ellipses	1 1 95% 0,95
Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set Stanby Power (Psb) in W Beam Angle in degrees for directional light source Parameters for LED and OLED light sources R9 colour rendering index value Survival factor [x,xx] The lumen maintenance factor [x,xx] Displacement factor (cos φ1) Colour consistency in McAdam ellipses	1 1 95% 0,95 5
Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set Stanby Power (Psb) in W Beam Angle in degrees for directional light source Parameters for LED and OLED light sources R9 colour rendering index value Survival factor [x,xx] The lumen maintenance factor [x,xx] Displacement factor (cos φ1) Colour consistency in McAdam ellipses Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage If yes then replacement claim (W)	1 1 95% 0,95 5
Peak luminous intensity (cd)Beam angle in degrees, or the range of beam angles that can be setStanby Power (Psb) in WBeam Angle in degrees for directional light sourceParameters for LED and OLED light sourcesR9 colour rendering index valueSurvival factor [x,xx]The lumen maintenance factor [x,xx]Displacement factor (cos φ1)Colour consistency in McAdam ellipsesClaims that an LED light source replaces a fluorescent light source without integrated ballast of a particular WattageIf yes then replacement claim (W)Flicker metric (Pst Lm) [x,x]	1 1 95% 0,95 5 No
Peak luminous intensity (cd)Beam angle in degrees, or the range of beam angles that can be setStanby Power (Psb) in WBeam Angle in degrees for directional light sourceParameters for LED and OLED light sourcesR9 colour rendering index valueSurvival factor [x,xx]The lumen maintenance factor [x,xx]Displacement factor (cos φ1)Colour consistency in McAdam ellipsesClaims that an LED light source replaces a fluorescent light source without integrated ballast of a particular WattageIf yes then replacement claim (W)Flicker metric (Pst Lm) [x,x]Stroboscopic effect metric (SVM) [X,X]	1 1 95% 0,95 5 No 0,0035
Peak luminous intensity (cd)Beam angle in degrees, or the range of beam angles that can be setStanby Power (Psb) in WBeam Angle in degrees for directional light sourceParameters for LED and OLED light sourcesR9 colour rendering index valueSurvival factor [x,xx]The lumen maintenance factor [x,xx]Displacement factor (cos φ1)Colour consistency in McAdam ellipsesClaims that an LED light source replaces a fluorescent light source without integrated ballast of a particular WattageIf yes then replacement claim (W)Flicker metric (Pst Lm) [x,x]Stroboscopic effect metric (SVM) [X,X]Displacement factor (cos φ1) for LED and OLED mains light sources LED/OLED	1 95% 0,95 5 No 0,0035 0,0015
Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set Stanby Power (Psb) in W Beam Angle in degrees for directional light source Parameters for LED and OLED light sources R9 colour rendering index value Survival factor [x,xx] The lumen maintenance factor [x,xx] Displacement factor (cos φ1) Colour consistency in McAdam ellipses Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage If yes then replacement claim (W) Flicker metric (Pst Lm) [x,x] Stroboscopic effect metric (SVM) [X,X] Displacement factor (cos φ1) for LED and OLED mains light sources LED/OLED Colour consistency in MacAdam ellipse steps for LED and OLED light sources	1 95% 0,95 5 No 0,0035 0,0015 0,95
Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set Stanby Power (Psb) in W Beam Angle in degrees for directional light source	1 95% 0,95 5 No 0,0035 0,0015 0,95 5
Peak luminous intensity (cd)Beam angle in degrees, or the range of beam angles that can be setStanby Power (Psb) in WBeam Angle in degrees for directional light sourceParameters for LED and OLED light sourcesR9 colour rendering index valueSurvival factor [x,xx]The lumen maintenance factor [x,xx]Displacement factor (cos φ1)Colour consistency in McAdam ellipsesClaims that an LED light source replaces a fluorescent light source without integrated ballast of a particular WattageIf yes then replacement claim (W)Flicker metric (Pst Lm) [x,x]Stroboscopic effect metric (SVM) [X,X]Displacement factor (cos φ1) for LED and OLED mains light sources LED/OLEDColour consistency in MacAdam ellipse steps for LED and OLED light sourcesFlicker metric (PstLM) for LED and OLED light sources	1 1 95% 0,95 5 No 0,0035 0,0015 0,95 5 0,0035

