

# NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A

Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE

Model identifier: 9110352

Type of light source: LED



## Product information Sheet

### General Information

Material number	9110352
Type	Pendant
Product segment	INDOOR

### Dimensions

Lenght (in cm)	64cm
Width (in cm)	44cm
Height (in cm)	120cm
Net Weight	

### Material & Colour

Enclosure Material	Aluminium & Acrylic
Colour	Gold
Adjustable	Yes

### Functionality

Switch Type	
Function	Dimmable
Battery	
USB Charger	

### Technical Information

Protection Degree	IP20
Protection Class	CLASS I
Mains Voltage	230V
max. Wattage	55.70W
Lumen	4441Lm
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	30000H
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	83,4
Rated Lamp Power (0,1W precision)	55.70W
Colour Tolerance (LED, SDCM)	


## Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tunable light source [yes/no]	No
Envelope [no/second/non-clear]	-
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	Yes

## General Product parameters

Energy consumption in on-mode (kWh/1000h)	55.70
Energy efficiency class	G
Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	4441.22lm
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3099K
On-mode power ( $P_{on}$ ), expressed in W [x,x]	55.70W
Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	0
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	83,4
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	2835*0.2W/120PCS/14.4M 3.45M

Spectral power distribution in the range 250 nm to 800 nm, at full-load



## Parameters for LED and OLED light sources

R9 colour rendering index value	11
Survival factor [x,xx]	0,9
The lumen maintenance factor [x,xx]	96%
Displacement factor ( $\cos \phi_1$ )	0,981
Colour consistency in McAdam ellipses	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	0,58
Stroboscopic effect metric (SVM) [X,X]	0,474
Pon in W	55.70W
Displacement factor ( $\cos \phi_1$ ) for LED and OLED mains light sources	0,981
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	
Flicker metric (PstLM) for LED and OLED light sources	0,58
Stroboscopic effect metric (SVM) for LED and OLED light sources	0,474
Excitation purity, only for CTLS, for the following colours and dominant wavelength within the given range: Blue 440nm - 490nm, Green 520nm - 570nm, Red 610nm - 670nm	

