


# NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A

Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE

Model identifier: 9115912

Type of light source: LED



## Product information Sheet

### General Information

Material number	9115912
Type	Wall Light
Product segment	INDOOR

### Dimensions

Diameter (in cm)	505*47mm
Width (in cm)	-
Height (in cm)	82mm
Cut Out (in cm)	
Net Weight	1.3Kg

### Material & Colour

Enclosure Material	Alumunioum&Acrylic
Colour	Sand White
Adjustable	Yes

### Functionality

Switch Type	
Function	-
Battery	No
USB Charger	No

### Technical Information

Protection Degree	IP20
Protection Class	I
Mains Voltage	220V
max. Wattage	2*12W
Lumen	1823
Equivalence With Incandescent Lamp (W)	0W
Colour Temperature	3000K
Nominal Lifetime (in h)	30000H
Switching Cycles	15000
Colour Rendering Index (Ra, CRI)	-
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	3

## Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	MLS
Connected light source (CLS) [yes/no]	Yes
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	No
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	Yes
Dimmable [yes/only with specific dimmers/no]	No

## General Product parameters

Energy consumption in on-mode (kWh/1000h)	6k
Energy efficiency class	F
Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1726.22LM
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	Single Value
On-mode power ( $P_{on}$ ), expressed in W [x,x]	2*12W
Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0W
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	0W
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	
Spectral power distribution in the range 250 nm to 800 nm, at full-load	
Beam Angle in degrees for directional light source	
Claim of equivalent power (c)	
If yes, equivalent power (W)	
Chromaticity coordinates (x and y)	X=0.4399 Y=0.4014

## Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	120

## Parameters for LED and OLED light sources

R9 colour rendering index value	5
Survival factor [x,xx]	
The lumen maintenance factor [x,xx]	
Displacement factor ( $\cos \phi_1$ )	
Colour consistency in McAdam ellipses	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	
Stroboscopic effect metric (SVM) for LED and OLED light sources/ LED/OLED	
Pon in W	

