

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 9122341
Type of light source: LED



Product information Sheet

General Information

Material number	9122341
Type	Bathroom Light
Product segment	INDOOR

Dimensions

Length (in cm)	51Cm
Width (in cm)	9.8Cm
Height (in cm)	7.5Cm
Height 2 (in cm)	
Cut Out (in cm)	
Net Weight (in cm)	1.85kg

Material & Colour

Enclosure Material	Aluminium & Acrylic & Metal
Colour	Chrome
Adjustable	

Functionality

Switch Type	-
Function	-
Battery	No
USB Charger	No

Technical Information


Protection Degree	IP44
Protection Class	I
Mains Voltage	220-240V
max. Wattage	20W
Lumen	1906
Equivalence With Incandescent Lamp (W)	-
Colour Temperature	3000K
Nominal Lifetime (in h)	50000H
Switching Cycles	
Colour Rendering Index (Ra, CRI)	≥80
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	3,2

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	No
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	No

General Product parameters

Energy consumption in on-mode (kWh/1000h)	20W
Energy efficiency class	F
The calculations performed with the parameters, including the determination of the energy class	F
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1907lm
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3118K
On-mode power (P_{on}), expressed in W [x,x]	21.1W
Standby power (P_{sb}), expressed in W and rounded to the second decimal	0
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	N/A
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	
Spectral power distribution in the range 250 nm to 800 nm, at full-load	



Claim of equivalent power (c)
If yes, equivalent power (W)

Chromaticity coordinates (x and y)

x=0.4268,y=0.3969

Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	
Standby Power (P_{sb}) in W	0

Parameters for LED and OLED light sources

R9 colour rendering index value	4
Survival factor [x,xx]	1
The lumen maintenance factor [x,xx]	96%
Displacement factor ($\cos \phi_1$)	0,85
Colour consistency in MacAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric ($P_{st} Lm$) [x,x]	0,019
Stroboscopic effect metric (SVM) [X,X]	0,003
Displacement factor ($\cos \phi_1$) for LED and OLED mains light sources LED/OLED	0,85
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	5
Flicker metric ($P_{st} LM$) for LED and OLED light sources	0,019
Stroboscopic effect metric (SVM) for LED and OLED light sources	0,003
P_{on} in W	21.1W

