

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A

Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE

Model identifier: 9180674

Type of light source: LED



Product information Sheet

General Information

Material number	9180674
Type	Pendant light
Product segment	INDOOR

Dimensions

Diameter (in cm)	70X6 Cm
Width (in cm)	
Height (in cm)	120 Cm
Net Weight	

Material & Colour

Enclosure Material	Iron & alu & acrylic
Colour	Gold
Adjustable	

Functionality

Switch Type	
Function	
Battery	
USB Charger	

Technical Information

Protection Degree	IP20
Protection Class	CLASS I
Mains Voltage	220-240V
max. Wattage	15.06W
Lumen	
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	30000H
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	82,6
Rated Lamp Power (0,1W precision)	15.06W
Colour Tolerance (LED, SDCM)	0,8


Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	-
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	No

General Product parameters

Energy consumption in on-mode (kWh/1000h)	15.06
Energy efficiency class	G
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1017.89lm
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3005K
On-mode power (P_{on}), expressed in W [x,x]	15.06W
Standby power (P_{sb}), expressed in W and rounded to the second decimal	0
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	82,6
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	"2835*0.2W*6PCS /1.2W 12PCS SS-12-24 MB 12W size : 68.5*35*23"

Spectral power distribution in the range 250 nm to 800 nm, at full-load



Parameters for LED and OLED light sources

R9 colour rendering index value	10
Survival factor [x,xx]	0,9
The lumen maintenance factor [x,xx]	96%
Displacement factor ($\cos \phi_1$)	0,841
Colour consistency in McAdam ellipses	0,8
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	0,177
Stroboscopic effect metric (SVM) [X,X]	0,05
P_{on} in W	15.06W
Displacement factor ($\cos \phi_1$) for LED and OLED mains light sources	0,841
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	0,8
Flicker metric (PstLM) for LED and OLED light sources	0,177
Stroboscopic effect metric (SVM) for LED and OLED light sources	0,05
Excitation purity, only for CTLS, for the following colours and dominant wavelength within the given range: Blue 440nm - 490nm, Green 520nm - 570nm, Red 610nm - 670nm	

