


NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 9180783
Type of light source: LED



Product information Sheet

General Information

Material number	9180783
Type	Pendant
Product segment	INDOOR

Dimensions

Diameter (in cm)	85cm
Width (in cm)	
Height (in cm)	H ₁ 31cm H ₂ 120cm
Net Weight	

Material & Colour

Enclosure Material	Metal & Acrylic
Colour	Black
Adjustable	Yes

Functionality

Switch Type	
Function	Dimmable
Battery	
Remote Control	Included

Technical Information

Protection Degree	IP20
Protection Class	CLASS I
Mains Voltage	230V
max. Wattage	66.70W
Lumen	5397Lm
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	30000H
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	83,0
Rated Lamp Power (0,1W precision)	66.70W
Colour Tolerance (LED, SDCM)	2,4


Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	-
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	Yes

General Product parameters

Energy consumption in on-mode (kWh/1000h)	66.70
Energy efficiency class	G
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	5397lm
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3163K
On-mode power (P_{on}), expressed in W [x,x]	66.70W
Standby power (P_{sb}), expressed in W and rounded to the second decimal	0
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	83,0
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	"2835*0.2W (4W+6W)*12PCS"

Spectral power distribution in the range 250 nm to 800 nm, at full-load



Parameters for LED and OLED light sources

R9 colour rendering index value	6
Survival factor [x,xx]	0,9
The lumen maintenance factor [x,xx]	96%
Displacement factor ($\cos \phi_1$)	0,954
Colour consistency in McAdam ellipses	2,4
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	0,177
Stroboscopic effect metric (SVM) [X,X]	0,050
Pon in W	66.70W
Displacement factor ($\cos \phi_1$) for LED and OLED mains light sources	0,954
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	2,4
Flicker metric (PstLM) for LED and OLED light sources	0,177
Stroboscopic effect metric (SVM) for LED and OLED light sources	0,050
Excitation purity, only for CTLS, for the following colours and dominant wavelength within the given range: Blue 440nm - 490nm, Green 520nm - 570nm, Red 610nm - 670nm	

