

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 9182371
Type of light source: LED & E14 Bulb Excluded



Product information Sheet

General Information

Material number	9182371
Type	Wall Lamp
Product segment	INDOOR

Dimensions

length (in cm)	19 Cm
Width (in cm)	16 Cm
Height (in cm)	30 Cm
Net Weight	0.6 kg

Material & Colour

Enclosure Material	Metal & Fabric Shade
Colour	White

Functionality

Switch Type	knife switch
Function	lighting
Battery	No

Technical Information

Protection Degree	IP20
Protection Class	I
Mains Voltage	230V
max. Wattage	LED 3W
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	30000h
Switching Cycles	on-off
Colour Rendering Index (Ra, CRI)	83,4
Rated Lamp Power (0,1W precision)	3W
Colour Tolerance (LED, SDCM)	±100K

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	No
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	No

General Product parameters

Energy consumption in on-mode (kWh/1000h)	3
Energy efficiency class	G
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	230 in sphere
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3000K
On-mode power (P_{on}), expressed in W [x,x]	3W
Standby power (P_{sb}), expressed in W and rounded to the second decimal	0.00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre): Height: Width: Depth:	
Spectral power distribution in the range 250 nm to 800 nm, at full-load	[graphic]
Claim of equivalent power (c)	[yes/-]
If yes, equivalent power (W)	
Chromaticity coordinates (x and y)	x=0.374, y=0.362

Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	

Parameters for LED and OLED light sources

R9 colour rendering index value [x]	23
Survival factor [x,xx]	1.00
The lumen maintenance factor [x,xx]	0,96
Displacement factor ($\cos \phi_1$)	
Colour consistency in McAdam ellipses	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	
Stroboscopic effect metric (SVM) [X,X]	
Pon in W	2,65
Stanby Power (Psb) in W	0
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	3,3

