

# NOVA LUCE

**Supplier's name or trade mark:** NOVA LUCE S.A

**Supplier's address:** SCHIMATARI VIOTIAS 32009, GREECE

**Model identifier:** 9280674

**Type of light source:** LED



## Product information Sheet

### General Information

Material number	9280674
Type	Table
Product segment	INDOOR

### Dimensions

Lenght (in cm)	28cm
Width (in cm)	9cm
Height (in cm)	52cm
Net Weight	

### Material & Colour

Enclosure Material	Metal & Acrylic
Colour	Black & Gold
Adjustable	

### Functionality

Switch Type	on/off SWITCH on line
Function	
Battery	
USB Charger	

### Technical Information

Protection Degree	IP20
Protection Class	CLASS III
Mains Voltage	230V
max. Wattage	8.92W
Lumen	
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	30000H
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	82,2
Rated Lamp Power (0,1W precision)	8.92W
Colour Tolerance (LED, SDCM)	0,8


## Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	-
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	No

## General Product parameters

Energy consumption in on-mode (kWh/1000h)	8.92
Energy efficiency class	G
Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	609.32lm
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	2992K
On-mode power ( $P_{on}$ ), expressed in W [x,x]	8.92W
Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	0
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	82,2
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	"2835*0.2W*6PCS /1.2W 6PCS HLV2412 TE 24V 12W"

Spectral power distribution in the range 250 nm to 800 nm, at full-load



## Parameters for LED and OLED light sources

R9 colour rendering index value	8
Survival factor [x,xx]	0,9
The lumen maintenance factor [x,xx]	96%
Displacement factor ( $\cos \phi_1$ )	0,520
Colour consistency in MacAdam ellipses	0,8
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	0,177
Stroboscopic effect metric (SVM) [X,X]	0,05
$P_{on}$ in W	8.92W
Displacement factor ( $\cos \phi_1$ ) for LED and OLED mains light sources	0,520
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	0,8
Flicker metric (PstLM) for LED and OLED light sources	0,177
Stroboscopic effect metric (SVM) for LED and OLED light sources	0,05
Excitation purity, only for CTLS, for the following colours and dominant wavelength within the given range: Blue 440nm - 490nm, Green 520nm - 570nm, Red 610nm - 670nm	

