

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 9333072
Type of light source: LED



Product information Sheet

General Information

Material number	9333072
Type	Pendant light
Product segment	INDOOR

Dimensions

Length (in cm)	60 Cm
Width (in cm)	- Cm
Height (in cm)	12 Cm
Net Weight	7,5 Kg

Material & Colour

Enclosure Material	Aluminium & Crystal
Colour	Chrome
Adjustable	No

Functionality

Switch Type	No
Function	LED
Battery	No
USB Charger	No

Technical Information

Protection Degree	IP20
Protection Class	CLASS I
Mains Voltage	AC 220-240V
max. Wattage	40W
Lumen	
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3500K
Nominal Lifetime (in h)	30000H
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	>80
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	<6


Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	No
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	Yes

General Product parameters

Energy consumption in on-mode (kWh/1000h)	40k
Energy efficiency class	E
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2505
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3500K
On-mode power (P_{on}), expressed in W [x,x]	39
Standby power (P_{sb}), expressed in W and rounded to the second decimal	
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	>80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	

Spectral power distribution in the range 250 nm to 800 nm, at full-load



Claim of equivalent power (c)	
If yes, equivalent power (W)	
Chromaticity coordinates (x and y)	x=0.4359 y=0.3996

Parameters for directional light sources

Peak luminous intensity (cd)	
Beam Angle in degrees for directional light source	120

Parameters for LED and OLED light sources

R9 colour rendering index value	
Survival factor [x,xx]	
The lumen maintenance factor [x,xx]	
Displacement factor (cos ϕ_1)	
Colour consistency in McAdam ellipses	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	No
Stroboscopic effect metric (SVM) [X,X]	<0.9
P_{on} in W	40

