


# NOVA LUCE

**Supplier's name or trade mark:** NOVA LUCE S.A  
**Supplier's address:** SCHIMATARI VIOTIAS 32009, GREECE  
**Model identifier:** 9511020  
**Type of light source:** LED



## Product information Sheet

### General Information

Material number	9511020
Type	Pendant
Product segment	INDOOR

### Dimensions

Diameter (in cm)	11cm
Width (in cm)	
Height (in cm)	120cm
Net Weight	

### Material & Colour

Enclosure Material	Aluminium & Acrylic
Colour	Gold
Adjustable	Adjustable Height

### Functionality

Switch Type	
Function	
Battery	
USB Charger	

### Technical Information


Protection Degree	IP20
Protection Class	I
Mains Voltage	230V
max. Wattage	7W
Lumen	
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3200K
Nominal Lifetime (in h)	30000H
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	86,8
Rated Lamp Power (0,1W precision)	7.0W
Colour Tolerance (LED, SDCM)	3,4

## Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tunable light source [yes/no]	No
Envelope [no/second/non-clear]	-
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	No

## General Product parameters

Energy consumption in on-mode (kWh/1000h)	7.0
Energy efficiency class	G
Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	344,54
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3200K
On-mode power ( $P_{on}$ ), expressed in W [x,x]	7.0W
Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	0
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	86,8
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	
Spectral power distribution in the range 250 nm to 800 nm, at full-load	



## Parameters for LED and OLED light sources

R9 colour rendering index value	43
Survival factor [x,xx]	0,9
The lumen maintenance factor [x,xx]	96%
Displacement factor ( $\cos \phi_1$ )	0,748
Displacement factor ( $\cos \phi_1$ ) for LED and OLED mains light sources	0,748
Colour consistency in MacAdam ellipses	3,4
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	3,4
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric ( $P_{st} Lm$ ) [x,x]	0,177
Flicker metric ( $P_{st} LM$ ) for LED and OLED light sources	0,177
Stroboscopic effect metric (SVM) [X,X]	0,05
Stroboscopic effect metric (SVM) for LED and OLED light sources	0,05
$P_{on}$ in W	6.91W
Excitation purity, only for CTLS, for the following colours and dominant wavelength within the given range: Blue 440nm - 490nm, Green 520nm - 570nm, Red 610nm - 670nm	

