

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 9853681
Type of light source: LED



Product information Sheet

General Information

| | |
|-----------------|---------|
| Material number | 9853681 |
| Type | Pendant |
| Product segment | INDOOR |

Dimensions

| | |
|--------------------|--------|
| Diameter (in cm) | 48cm |
| Width (in cm) | |
| Height (in cm) | 150cm |
| Net Weight (in cm) | 1.88kg |

Material & Colour

| | |
|--------------------|--------------------|
| Enclosure Material | Aluminum & Acrylic |
| Colour | Sandy White |
| Adjustable | Yes |

Functionality

| | |
|-------------|----------------|
| Switch Type | |
| Function | Triac Dimmable |
| Battery | |
| USB Charger | |

Technical Information

| | |
|--|--------|
| Protection Degree | IP20 |
| Protection Class | |
| Mains Voltage | 230V |
| max. Wattage | 38W |
| Lumen | 2175Lm |
| Equivalence With Incandescent Lamp (W) | |
| Colour Temperature | 3000K |
| Nominal Lifetime (in h) | 75000h |
| Switching Cycles | |
| Colour Rendering Index (Ra, CRI) | 80 |
| Rated Lamp Power (0,1W precision) | |
| Colour Tolerance (LED, SDCM) | |

Product information

| | |
|---|------|
| Lighting technology used [LED/OLED/MIXED/OTHER] | LED |
| Non-directional or directional [NDLS/DLS] | NDLS |
| Mains or non-mains [MLS/NMLS] | NMLS |
| Connected light source (CLS) [yes/no] | No |
| Colour-tuneable light source [yes/no] | No |
| Envelope [no/second/non-clear] | No |
| High luminance light source [yes/no] | No |
| Anti-glare shield [yes/no] | No |
| Dimmable [yes/only with specific dimmers/no] | No |

General Product parameters

| | |
|---|----------------|
| Energy consumption in on-mode (kWh/1000h) | 38 |
| Energy efficiency class | E |
| The calculations performed with the parameters, including the determination of the energy class | |
| Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 1300 in sphere |
| Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set : | 3000K |
| On-mode power (P_{on}), expressed in W [x,x] | 10,2W |
| Standby power (P_{sb}), expressed in W and rounded to the second decimal | |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | |
| Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set | 80 |
| Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre): | 454*13*1 |
| Spectral power distribution in the range 250 nm to 800 nm, at full-load | |
| Claim of equivalent power (c) | |
| If yes, equivalent power (W) | |
| Chromaticity coordinates (x and y) | 0.440/0.403 |

Parameters for directional light sources

| | |
|--|--|
| Peak luminous intensity (cd) | |
| Beam angle in degrees, or the range of beam angles that can be set | |
| Stanby Power (P_{sb}) in W | |
| Beam Angle in degrees for directional light source | |

Parameters for LED and OLED light sources

| | |
|--|------|
| R9 colour rendering index value | 0 |
| Survival factor [x,xx] | 0.9 |
| The lumen maintenance factor [x,xx] | 0.96 |
| Displacement factor ($\cos \phi_1$) | |
| Colour consistency in McAdam ellipses | 6 |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage | |
| If yes then replacement claim (W) | |
| Flicker metric ($P_{st} Lm$) [x,x] | |
| Stroboscopic effect metric (SVM) [X,X] | |
| Displacement factor ($\cos \phi_1$) for LED and OLED mains light sources LED/OLED | |
| Colour consistency in MacAdam ellipse steps for LED and OLED light sources | |
| Flicker metric ($P_{st} LM$) for LED and OLED light sources | |
| Stroboscopic effect metric (SVM) for LED and OLED light sources | |
| P_{on} in W | |

