


# NOVA LUCE

**Supplier's name or trade mark:** NOVA LUCE S.A  
**Supplier's address:** SCHIMATARI VIOTIAS 32009, GREECE  
**Model identifier:** 9879106  
**Type of light source:** LED



## Product information Sheet

### General Information

Material number	9879106
Type	Step Light
Product segment	INDOOR

### Dimensions

Length (in cm)	10 Cm
Width (in cm)	4.75 Cm
Height (in cm)	10 Cm
Cut Out (in cm)	10.3 x 10.3 Cm
Net Weight	0,5 Kg

### Material & Colour

Enclosure Material	Gypsum
Colour	White
Adjustable Brackets	Yes

### Functionality

Switch Type	No
Function	LED
Battery	No
Driver Included	Yes (Waiberlon)

### Technical Information

Protection Degree	IP20
Protection Class	
Mains Voltage	
max. Wattage	1W Cree
Lumen	
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	

## Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	
Mains or non-mains [MLS/NMLS]	
Connected light source (CLS) [yes/no]	
Colour-tuneable light source [yes/no]	
Envelope [no/second/non-clear]	
High luminance light source [yes/no]	
Anti-glare shield [yes/no]	
Dimmable [yes/only with specific dimmers/no]	No

## General Product parameters

Energy consumption in on-mode (kWh/1000h)	1Kwr
Energy efficiency class	F
Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	
On-mode power ( $P_{on}$ ), expressed in W [x,x]	
Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	
Spectral power distribution in the range 250 nm to 800 nm, at full-load	

Claim of equivalent power (c)	
If yes, equivalent power (W)	
Chromaticity coordinates (x and y)	

## Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	
Beam Angle in degrees for directional light source	

## Parameters for LED and OLED light sources

R9 colour rendering index value	
Survival factor [x,xx]	
The lumen maintenance factor [x,xx]	
Displacement factor ( $\cos \phi_1$ )	
Colour consistency in McAdam ellipses	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	
Stroboscopic effect metric (SVM) [X,X]	
Pon in W	

