

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 9952314
Type of light source: LED



Product information Sheet

General Information

Material number	9952314
Type	CEILING FAN
Product segment	INDOOR

Dimensions

Diameter (in cm)	132 Cm
Width (in cm)	- Cm
Height (in cm)	35-48 Cm
Net Weight	5.8 KG

Material & Colour

Enclosure Material	Steel & Glass & Oak Wood
Colour	Matt White

Functionality

Switch Type	Remote Control
Function	See the functions in Instructions Manuals
Battery	No

Technical Information

Protection Degree	IP20
Protection Class	I
Mains Voltage	220-240V
max. Wattage	25W
Lumen	-
Equivalence With Incandescent Lamp (W)	-
Colour Temperature	3000K
Nominal Lifetime (in h)	210000 hrs
Switching Cycles	yes
Colour Rendering Index (Ra, CRI)	-
UGR	-
Rated Lamp Power (0,1W precision)	25W
Colour Tolerance (LED, SDCM)	-

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	-
Mains or non-mains [MLS/NMLS]	-
Connected light source (CLS) [yes/no]	-
Colour-tunable light source [yes/no]	-
Envelope [no/second/non-clear]	-
High luminance light source [yes/no]	-
Anti-glare shield [yes/no]	-
Dimmable [yes/only with specific dimmers/no]	-

General Product parameters

Energy consumption in on-mode (kWh/1000h)	25
Energy efficiency class	
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	-
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	
On-mode power (P_{on}), expressed in W [x,x]	-
Standby power (P_{sb}), expressed in W and rounded to the second decimal	No
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	-
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any Height/Width /Depth:	-
Spectral power distribution in the range 250 nm to 800 nm, at full-load	-
Claim of equivalent power (c)	-
If yes, equivalent power (W)	-
Chromaticity coordinates (x and y)	

Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	120°

Parameters for LED and OLED light sources

R9 colour rendering index value	-
Survival factor [x,xx]	-
The lumen maintenance factor [x,xx]	-
Displacement factor (cos ϕ_1)	-
Colour consistency in McAdam ellipses	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	
Stroboscopic effect metric (SVM) [X,X]	
Beam Angle in degrees for directional light source	
The reference control settings, and instructions on how they can be implemented, where applicable	See Instructions Manuals
Instructions on how to remove lighting control parts and/or non-lighting parts, if any, or how to switch them off or minimise their power consumption during light source testing	See Instructions Manuals
Specific precautions that shall be taken when the model is assembled, installed, maintained or tested	See Instructions Manuals

