

# NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A  
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE  
Model identifier: 9081210  
Type of light source: LED



## Product information Sheet

### General Information

|                 |             |
|-----------------|-------------|
| Material number | 9081210     |
| Type            | Lamp holder |
| Product segment | Indoor      |

### Dimensions

|                  |       |
|------------------|-------|
| Diameter (in cm) | 45 Cm |
| Width (in cm)    |       |
| Height (in cm)   | 6 Cm  |
| Net Weight       |       |

### Material & Colour

|                    |                          |
|--------------------|--------------------------|
| Enclosure Material | Steel +Acrylic+Aluminium |
| Colour             | BLACK                    |
| Adjustable         | LED                      |

### Functionality

|             |        |
|-------------|--------|
| Switch Type | On/Off |
| Function    |        |
| Battery     |        |
| USB Charger |        |

### Technical Information

|  |          |
|--|----------|
| Protection Degree                      | IP20     |
| Protection Class                       | CLASS II |
| Mains Voltage                          | 220 V    |
| max. Wattage                           | 30 W     |
| Lumen                                  |          |
| Equivalence With Incandescent Lamp (W) |          |
| Colour Temperature                     | 3000K    |
| Nominal Lifetime (in h)                | 20000    |
| Switching Cycles                       | >15000   |
| Colour Rendering Index (Ra, CRI)       | 80       |
| Rated Lamp Power (0,1W precision)      | 30       |
| Colour Tolerance (LED, SDCM)           | LED      |

## Product information

|   |       |
|---|-------|
| Lighting technology used [LED/OLED/MIXED/OTHER] | LED   |
| Non-directional or directional [NDLS/DLS]       | NDLS  |
| Mains or non-mains [MLS/NMLS]                   | Mains |
| Connected light source (CLS) [yes/no]           | Yes   |
| Colour-tuneable light source [yes/no]           | No    |
| Envelope [no/second/non-clear]                  | No    |
| High luminance light source [yes/no]            | No    |
| Anti-glare shield [yes/no]                      | Yes   |
| Dimmable [yes/only with specific dimmers/no]    | No    |

## General Product parameters

|  |         |
|--|---------|
| Energy consumption in on-mode (kWh/1000h)  | 30      |
| Energy efficiency class  | F       |
| The calculations performed with the parameters, including the determination of the energy class  | 2400    |
| Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)                 | 3000    |
| Correlated colour temperature, rounded to the nearest 100 K,<br>or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set : | 3000    |
| On-mode power ( $P_{on}$ ), expressed in W [x,x]   | 30      |
| Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   |         |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  |         |
| Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set  | 80      |
| Outer dimensions without separate control gear, lighting control parts<br>and non-lighting control parts, if any (millimetre):                                 | D45*6cm |
| Spectral power distribution in the range 250 nm to 800 nm, at full-load  |         |
| Claim of equivalent power (c)  | No      |
| If yes, equivalent power (W)   |         |
| Chromaticity coordinates (x and y)   |         |

## Parameters for directional light sources

|  |  |
|--|--|
| Peak luminous intensity (cd)                                       |  |
| Beam angle in degrees, or the range of beam angles that can be set |  |
| Beam Angle in degrees for directional light source                 |  |

## Parameters for LED and OLED light sources

|  |        |
|--|--------|
| R9 colour rendering index value  | 1      |
| Survival factor [x,xx]   | 1      |
| The lumen maintenance factor [x,xx]  | 95%    |
| Displacement factor ( $\cos \phi_1$ )  | 0.95   |
| Displacement factor ( $\cos \phi_1$ ) for LED and OLED mains light sources   | 0.95   |
| Colour consistency in McAdam ellipses  | 5      |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage | No     |
| Colour consistency in MacAdam ellipse steps for LED and OLED light sources   | 5      |
| Flicker metric (Pst Lm) [x,x]  | 0.0035 |
| Flicker metric (PstLM) for LED and OLED light sources  | 0.0035 |
| Stroboscopic effect metric (SVM) [X,X]   | 0.0015 |
| Stroboscopic effect metric (SVM) for LED and OLED light sources  |        |
| $P_{on}$ in W  | 30     |
| The calculations performed with the parameters, including the determination of the energy class                        | F      |

