

# NOVA LUCE

**Supplier's name or trade mark:** NOVA LUCE S.A  
**Supplier's address:** SCHIMATARI VIOTIAS 32009, GREECE  
**Model identifier:** 9695235  
**Type of light source:** LED



## Product information Sheet

### General Information

Material number	9695235
Type	Pendant
Product segment	INDOOR

### Dimensions

Diameter (in cm)	52.5cm
Width (in cm)	-
Height (in cm)	200cm
Height 2 (in cm)	-
Cut Out (in cm)	-
Net Weight (in cm)	-

### Material & Colour

Enclosure Material	Aluminium & Acrylic
Colour	Satin Gold
Adjustable	

### Functionality

Switch Type	-
Function	-
Battery	No
USB Charger	No

### Technical Information

Protection Degree	IP20
Protection Class	-
Mains Voltage	230V
max. Wattage	32W
Lumen	3925lm
Equivalence With Incandescent Lamp (W)	-
Colour Temperature	3000K
Nominal Lifetime (in h)	-
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	Ra= 82.2
Rated Lamp Power (0,1W precision)	-
Colour Tolerance (LED, SDCM)	

## Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	-
Connected light source (CLS) [yes/no]	-
Colour-tuneable light source [yes/no]	-
Envelope [no/second/non-clear]	-
High luminance light source [yes/no]	-
Anti-glare shield [yes/no]	-
Dimmable [yes/only with specific dimmers/no]	No

## General Product parameters

Energy consumption in on-mode (kWh/1000h)	32W
Energy efficiency class	A+
Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	-
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3925K
On-mode power ( $P_{on}$ ), expressed in W [x,x]	32W
Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	-
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	Ra= 82.2
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	-
Spectral power distribution in the range 250 nm to 800 nm, at full-load	-
Beam Angle in degrees for directional light source	-
Claim of equivalent power (c)	-
If yes, equivalent power (W)	-
Chromaticity coordinates (x and y)	x=0.4488 y=0.4063

## Parameters for directional light sources

Peak luminous intensity (cd)	-
Beam angle in degrees, or the range of beam angles that can be set	-

## Parameters for LED and OLED light sources

R9 colour rendering index value	Ra= 82.2
Survival factor [x,xx]	-
The lumen maintenance factor [x,xx]	-
Displacement factor ( $\cos \phi_1$ )	-
Colour consistency in McAdam ellipses	-
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage If yes then replacement claim (W)	-
Flicker metric (Pst Lm) [x,x]	-
Stroboscopic effect metric (SVM) for LED and OLED light sources/ LED/OLED	-
Pon in W	-

