




Product Datasheet

02 Recessed Spots Fixed LED>The COB IP54 Dark Light Range

10108H/B/W



8W COB LED Dark light recessed Spot, IP54.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Dimensions




Downloads









Physical Specification

Item Group	02 Recessed Spots Fixed LED
Family	The COB IP54 Dark Light Range
Order Code	10108H/B/W
Colour	Black
Material	Die Cast
Shape	Circular
Height	55mm
Diameter	88mm
Cutout Hole Diameter	75mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes

Outdoor	Yes
Adjustable	No
lectrical Characteristics	
lectrical Griafacteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	200mA
Voltage	38V
Safety Class	
Power(Watts)	7,6W
IP Rating	IP54
Light Source	LED built in
LED Type	СОВ
LED Brand	Bridgelux
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	5-8,4W
Power Factor	0,9
Constant Current	Yes
200mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KEGU
Illumination Data	
	200014
Colour Temperature	3000K
Colour Temperature Lumen Output	600lm
Colour Temperature Lumen Output Light Efficiency	600lm 75lm/W
Colour Temperature Lumen Output Light Efficiency CRI	600lm 75lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	600lm 75lm/W
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	600lm 75lm/W 90 36°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	600lm 75lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	600lm 75lm/W 90 36°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	600lm 75lm/W 90 36°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	600lm 75lm/W 90 36°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info	600lm 75lm/W 90 36° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Pcs/Carton	600lm 75lm/W 90 36° Yes

Certification & Warranty

Warranty	5 Years
Weee Directive	Yes



