

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A

Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE

Model identifier: 9695223

Type of light source: LED



Product information Sheet

General Information

Material number	9695223
Type	Pendant light
Product segment	INDOOR

Dimensions

Diameter (in cm)	39 Cm
Width (in cm)	
Height (in cm)	150 Cm
Net Weight	

Material & Colour

Enclosure Material	Iron & alu & Acid White glass shade
Colour	Satin Gold
Adjustable	

Functionality

Switch Type	
Function	Dimmable
Battery	
USB Charger	


Technical Information

Protection Degree	IP20
Protection Class	CLASS I
Mains Voltage	220-240V
max. Wattage	25.81W
Lumen	
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	30000H
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	81,8
Rated Lamp Power (0,1W precision)	25.81W
Colour Tolerance (LED, SDCM)	

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	-
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	Yes

General Product parameters

Energy consumption in on-mode (kWh/1000h)	25.81
Energy efficiency class	G
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2549.73lm
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3062K
On-mode power (P_{on}), expressed in W [x,x]	25.81W
Standby power (P_{sb}), expressed in W and rounded to the second decimal	0
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	81,8
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	"A:2835*0.2W/56pcs/*3PCS B:2835*0.2W/49pcs/*2PCS"
Spectral power distribution in the range 250 nm to 800 nm, at full-load	

Parameters for LED and OLED light sources

R9 colour rendering index value	3
Survival factor [x,xx]	0,9
The lumen maintenance factor [x,xx]	96%
Displacement factor ($\cos \phi_1$)	0,955
Colour consistency in McAdam ellipses	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	0
Stroboscopic effect metric (SVM) [X,X]	0,051
Pon in W	25.81W
Displacement factor ($\cos \phi_1$) for LED and OLED mains light sources	0,936
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	
Flicker metric (PstLM) for LED and OLED light sources	0
Stroboscopic effect metric (SVM) for LED and OLED light sources	0,051
Excitation purity, only for CTLS, for the following colours and dominant wavelength within the given range: Blue 440nm - 490nm, Green 520nm - 570nm, Red 610nm - 670nm	