

Product Datasheet

www.1-light.eu

06 Downlights Fixed LED>The Frameless IP65 Range

10115CF/W



15W LED frameless downlight, IP65. Suitable for Indoor/Outdoor installation and bathroom.

Complete with 500mA driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions



Gallery



Related items







050146/W

Physical Specification

Item Group

06 Downlights Fixed LED

Family

The Frameless IP65 Range


Order Code	10115CF/W
Colour	White
Material	Die Cast
Diffuser Material	PC
Shape	Circular
Height	22mm
Diameter	155mm
Cutout Hole Diameter	135mm
Recessed Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8
Electrical Characteristics Gear	External-Included
Electrical Characteristics Gear Fitting + Driver	
Electrical Characteristics Gear Fitting + Driver Input Voltage	220-240V
Electrical Characteristics Gear Fitting + Driver	
Electrical Characteristics Gear Fitting + Driver Input Voltage 50 Hz	220-240V Yes
Electrical Characteristics Gear Fitting + Driver Input Voltage 50 Hz 60 Hz	220-240V Yes
Electrical Characteristics Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class	220-240V Yes Yes
Electrical Characteristics Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts)	220-240V Yes Yes IIIIIIIIIIIIIIIIIIIIIIIIIIIIII
Electrical Characteristics Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating	220-240V Yes Yes 15W IP65
Electrical Characteristics Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source	220-240V Yes Yes 15W IP65 LED built in
Electrical Characteristics Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable	220-240V Yes Yes In the state of the state o
Electrical Characteristics Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable	220-240V Yes Yes In the state of the state o

Input Current	500mA
Voltage	22,5V
Safety Class	ŢII]
Power(Watts)	11,25W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 4014
LED Brand	Zhaochi
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	8,5-12W
Power Factor	0,9
Constant Current	Yes
500mA	17-24V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Kegu
Ilumination Data	
Oalessa Tanasasat	000014
Colour Temperature	3000K
Lumen Output	1650lm
Light Efficiency	110lm/W
CRI	80

Beam Angle	120°
Illumination Diagram	

Packing Info	
Box Length	21cm
Box Width	19,5cm
Box Height	3cm
Box Weight	0.420kg
Pcs/Carton	20
Carton Length	43cm
Carton Width	37cm
Carton Height	22cm
Carton Weight	9,4Kg
Barcode	5291889057109
HS Code	9405413990

Energy Label



Energy Class F

Energy Consumption 15kWh/1000h

Certification & Warranty

switch to one light!

