

13 Wall & Ceiling LED>The SMD Cylinders Aluminium

12115L/B/W



15W SMD LED ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The SMD Cylinders Aluminium
Order Code	12115L/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	100mm
Diameter	130mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

15W

IP Rating

IP40

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

300mA

Voltage

45V

Power(Watts)

13,5W

IP Rating

IP20

Light Source

LED built in

LED Type

SMD 5630

LED Brand

Samsung

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)


9,5-15W

Power Factor

0,9

Constant Current	Yes
350mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	XY

Illumination Data

Colour Temperature	3000K
Lumen Output	1280lm
Light Efficiency	85,33lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

Packing Info

Box Length	14cm
Box Width	14cm
Box Height	11cm
Box Weight	0.558kg
Pcs/Carton	36
Barcode	5291889062110
HS Code	9405409900

Warranty

3 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

