

13 Wall & Ceiling LED>The Hidden Light Cylinders Range

12116FD/B/BS



16W LED Hidden Light Cylinders Range.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The Hidden Light Cylinders Range
Order Code	12116FD/B/BS
Colour	Black-Brass
Material	Die Cast
Shape	Circular
Height	80mm
Diameter	175mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear		Built In	
Fitting + Driver			
Input Voltage		220-240V	
50 Hz		Yes	
60 Hz		Yes	
Safety Class			
Power(Watts)		16W	
IP Rating		IP20	
Light Source		LED built in	
Dimmable		No	
F Mark			

Fitting			
Input Type		Constant Current	
Input Current		300mA	
Voltage		50V	
Power(Watts)		15W	
IP Rating		IP20	
Light Source		LED built in	
LED Type		SMD 2835	
LED Brand		Bridgelux	

Gear			
Gear Type		Led Driver	
Input Voltage		220-240V	
50 Hz		Yes	
60 Hz		Yes	
Power(Watts)		13,5-18W	
Power Factor		0,9	

Constant Current
300mA
IP Rating
Safety Class
Dimmable
Housing Material
Brand

Yes
45-60V
IP20

No
Plastic
KEGU

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Illumination Diagram
Dark Light

3000K
800lm
50lm/W
80

Yes

Packing Info

Box Length
Box Width
Box Height
Box Weight
Pcs/Carton
Barcode
HS Code

18cm
18cm
8,5cm
0.795kg
20
5291889068464
9405409900

Warranty

3 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

