

Product Datasheet

13 Wall & Ceiling LED>The COB LED Indoor Cylinders Aluminium

12130LA/W/W



30W COB LED ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



| Downloads | Dimensions |
|------------------------|-------------------------|
| | 198mm - 138mm - |
| Physical Specification | |

Item Group13 Wall & Ceiling LEDFamilyThe COB LED Indoor Cylinders AluminiumOrder Code12130LA/W/WColourWhiteMaterialAluminiumShapeCircularHeight138mm

| Diameter | 198mm |
|--------------|-------|
| Surface Wall | Yes |
| Indoor | Yes |
| Adjustable | No |



| Gear | Built In |
|------------------|--------------|
| | |
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | |
| Power(Watts) | 30W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark | F |

Fitting

| Input Type | Constant Current |
|---------------|------------------|
| Input Current | 700mA |
| Voltage | 40V |
| Power(Watts) | 29,4W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | СОВ |
| LED Brand | Philips |

Gear

| Gear Type | Lea Driver |
|---------------|------------|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 19-30,4W |
| Power Factor | 0,9 |
| | |



| Constant Current | Yes |
|------------------|---------|
| 700mA | 27-42V |
| IP Rating | IP20 |
| Safety Class | |
| Dimmable | No |
| Housing Material | Plastic |

Illumination Data

| Colour Temperature | 3000K |
|----------------------|-----------|
| Lumen Output | 2500lm |
| Light Efficiency | 83,33lm/W |
| CRI | 80 |
| Beam Angle | 50° |
| Illumination Diagram | |

Packing Info

| Box Weight | 1.000kg |
|------------|---------------|
| Pcs/Carton | 12 |
| Barcode | 5291889044925 |
| HS Code | 9405409900 |

Certification & Warranty



Weee Directive

switch to one light!



