

# NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A

Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE

Model identifier: 9695258

Type of light source: LED



## Product information Sheet

### General Information

Material number	9695258
Type	Pendant
Product segment	INDOOR

### Dimensions

Diameter (in cm)	52cm
Width (in cm)	
Height (in cm)	150cm
Net Weight	

### Material & Colour

Enclosure Material	Aluminium & Glass
Colour	Gold & Black
Adjustable	Adjustable Height

### Functionality

Switch Type	
Function	
Battery	
USB Charger	

### Technical Information

Protection Degree	IP20
Protection Class	
Mains Voltage	230V
max. Wattage	61W
Lumen	
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	30000H
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	

## Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	-
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	No

## General Product parameters

Energy consumption in on-mode (kWh/1000h)

Energy efficiency class

Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)

Correlated colour temperature, rounded to the nearest 100 K,  
or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :

On-mode power ( $P_{on}$ ), expressed in W [x,x]

Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal

0

Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal

0

Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set

Outer dimensions without separate control gear, lighting control parts  
and non-lighting control parts, if any (millimetre):

Spectral power distribution in the range 250 nm to 800 nm, at full-load

## Parameters for LED and OLED light sources

R9 colour rendering index value

Survival factor [x,xx]

The lumen maintenance factor [x,xx]

Displacement factor ( $\cos \phi_1$ )

Colour consistency in McAdam ellipses

Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage

If yes then replacement claim (W)

Flicker metric (Pst Lm) [x,x]

Stroboscopic effect metric (SVM) [X,X]

Pon in W

Displacement factor ( $\cos \phi_1$ ) for LED and OLED mains light sources

Colour consistency in MacAdam ellipse steps for LED and OLED light sources

Flicker metric (PstLM) for LED and OLED light sources

Stroboscopic effect metric (SVM) for LED and OLED light sources

Excitation purity, only for CTLS, for the following colours and dominant wavelength  
within the given range: Blue 440nm - 490nm, Green 520nm - 570nm, Red 610nm - 670nm

