

Product Datasheet

www.1-light.eu

04 Recessed Spots Adjustable LED>The Interchangable Rings Range

51112H/W/W

Aluminium



12W COB LED adjustable recessed spot with interchargeable rings.

Ring must be ordered separately.

Complete with 300mA driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads










Dimensions



Must be ordered separately







050088/BS



050088/G



050088/W



050088A/W

Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The Interchangable Rings Range Aluminium
Order Code	51112H/W/W
Colour	White
Material	Aluminium
Shape	Rectangular

Length	108mm
Width	108mm
Height	95mm
Cutout Hole Width	95mm
Cutout Hole Length	95mm
Recessed Ceiling	Yes
Depth Required	120mm
Indoor	Yes
Adjustable	1 Direction
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	12W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	36V
Safety Class	
Power(Watts)	10,8V
IP Rating	IP20

Light Source	LED built in
LED Type	СОВ
LED Brand	Cree
LED Number	1
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	9-12W
Power Factor	0,9
Constant Current	Yes
300mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Brand	Eaglerise
Illumination Data	
Colour Temperature	3000K
Lumen Output	940lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	60°
Illumination Diagram	
Packing Info	
Box Length	12cm

Box Width	12cm
Box Height	12cm
Box Weight	0,401Kg
Pcs/Carton	30
Barcode	5291889051343
HS Code	9405409900

Certification & Warranty Warranty 3 Years

Weee Directive Yes



