



# **Product Datasheet**

## 15 Plafo>The LED Slim Plafo Range Round

# 62022B/W/W



25W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



#### Gallery



#### **Physical Specification**

Item Group	15 Plafo
Family	The LED Slim Plafo Range Round
Order Code	62022B/W/W
Colour	White
Material	PC
Shape	Circular
Height	60mm


Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
lectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	40V
Power(Watts)	24W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	160
F Mark	F

330mm

Diameter

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	15-25,2W
Power Factor	0,9
Constant Current	Yes
600mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
Illumination Data	
	3000K
Colour Temperature	3000K 2000lm
Colour Temperature  Lumen Output	2000lm
Colour Temperature  Lumen Output  Light Efficiency	2000lm 80lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	2000lm
Colour Temperature  Lumen Output  Light Efficiency	2000lm 80lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	2000lm 80lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	2000lm 80lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	2000lm 80lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	2000lm 80lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length	2000lm 80Im/W 80 34cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width	2000lm  80lm/W  80  34cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	2000lm  80lm/W  80  34cm  7,5cm

### Energy Label



#### Certification & Warranty

Warranty 2 Years

Weee Directive Yes

# switch to one light!

