

14 Plafo>The Ultra Slim LED Floating Plafo Aluminium

62140FB/W/W



40W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads







Dimensions




Physical Specification

Item Group	14 Plafo
Family	The Ultra Slim LED Floating Plafo Aluminium
Order Code	62140FB/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	55mm
Diameter	400mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No


Gear		External-Included
Fitting + Driver		
Input Voltage		220-240V
50 Hz		Yes
60 Hz		Yes
Safety Class		
Power(Watts)		40W
IP Rating		IP20
Light Source		LED built in
Dimmable		No
F Mark		

Fitting		
Input Type		Constant Current
Input Current		1000mA
Voltage		39V
Safety Class		
Power(Watts)		39W
IP Rating		IP20
Light Source		LED built in
LED Type		SMD 2835
LED Brand		Sanan
F Mark		

Gear		
Gear Type		Led Driver
Input Voltage		220-240V
50 Hz		Yes
60 Hz		Yes

Power(Watts)	25-42W
Power Factor	0,9
Constant Current	Yes
1000mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	40°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Cable
Fast Connector	Yes
Fast Connector Type	Other
Brand	Lifud

Illumination Data

Colour Temperature	3000K
Lumen Output	3500lm
Light Efficiency	87,5lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	2.850kg
Pcs/Carton	4
Barcode	5291889057406
HS Code	9405413990

Warranty

3 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

