



## **Product Datasheet**

## 14 Plafo>The LED Plafo Outdoor Square Plastic

## 67282BN/G/W



30W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads










Dimensions



**Physical Specification** 

Item Group	14 Plafo
Family	The LED Plafo Outdoor Square Plastic
Order Code	67282BN/G/W
Colour	Grey
Material	Plastic
Diffuser Material	PC
Shape	Rectangular
Length	400mm
Width	400mm
Height	83mm
Surface Ceiling	Yes
Indoor	Yes

Outdoor	Yes
Adjustable	No
IK Rating	8
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	38V
Power(Watts)	28W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	144
F Mark	F
Gear	

Input Voltage         220-240V           50 Hz         Yes           60 Hz         Yes           Power(Watts)         18,2-30W           Power Factor         0,9           Constant Current         Yes           700mA         26-43,5V           IP Rating         IP20           Safety Class         □           Dimmable         No	
Fower(Watts)  Power Factor  Constant Current  Yes  700mA  PRating  IP20  Safety Class	
Power(Watts)18,2-30WPower Factor0,9Constant CurrentYes700mA26-43,5VIP RatingIP20Safety Class□	
Power Factor 0,9  Constant Current Yes  700mA 26-43,5V  IP Rating IP20  Safety Class	
Constant Current  700mA  26-43,5V  IP Rating  Safety Class	
700mA 26-43,5V  IP Rating IP20  Safety Class	
IP Rating  Safety Class	
Safety Class	
Dimmable No	
Housing Material Plastic	
Output Terminal Connector	
Brand	
Illumination Data  Colour Temperature 3000K	
Lumen Output 1800lm	
Light Efficiency 60lm/W	
CRI 80	
Illumination Diagram	
Packing Info	
acking into	
Box Length 41cm	
Box Width 41cm	
Box Height 10,5cm	
Box Weight 2.500kg	
Pcs/Carton 4	
Barcode 5291889043454	4

## Certification & Warranty

Warranty	2 Years
Weee Directive	Yes



