



Product Datasheet

14 Plafo>The LED Plafo Outdoor Square Plastic

67282N/G/W



16W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.









→ 1 IP65 IK 80 CRI CE

Downloads










Dimensions



Physical Specification

Item Group	14 Plafo
Family	The LED Plafo Outdoor Square Plastic
Order Code	67282N/G/W
Colour	Grey
Material	Plastic
Diffuser Material	PC
Shape	Rectangular
Length	221mm
Width	221mm
Height	57mm
Surface Ceiling	Yes
Indoor	Yes

Outdoor	Yes
Adjustable	No
IK Rating	8
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	30V
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	81
F Mark	F
Gear	

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	8,5-16W
Power Factor	0,9
Constant Current	Yes
500mA	19-32V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
Illumination Data	
Colour Temperature	3000K
Colour Temperature Lumen Output	3000K 960lm
Lumen Output	960lm
Lumen Output Light Efficiency	960lm 60lm/W
Lumen Output Light Efficiency CRI	960lm 60lm/W
Lumen Output Light Efficiency CRI	960lm 60lm/W
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info	960lm 60lm/W 80
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length	960lm 60lm/W 80
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width	960lm 60lm/W 80 23cm
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height	960lm 60lm/W 80 23cm 23cm 6,5cm
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	960lm 60lm/W 80 23cm 23cm 6,5cm
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight Pcs/Carton	960lm 60lm/W 80 23cm 23cm 6,5cm 0.860kg
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight Pcs/Carton Barcode	960lm 60lm/W 80 23cm 23cm 6,5cm 0.860kg 10
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight Pcs/Carton	960lm 60lm/W 80 23cm 23cm 6,5cm 0.860kg

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes



