


Product Datasheet

www.1-light.eu

13 Wall & Ceiling LED>Window Frame Illumination

67454/AN/W



6W LED for window frame illumination, IP65.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Gallery



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Window Frame Illumination
Order Code	67454/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	140mm

Width	95mm
Height	62mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Outdoor	Yes
IK Rating	8
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes

Yes

6W

IP65

LED built in

60 Hz

Safety Class

Power(Watts)

IP Rating

Light Source

Dimmable

F Mark

Fitting

Input Type

Voltage

IP Rating

Light Source

LED Type

Input Current

Power(Watts)

LED Brand	Cree
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	3-6W
Power Factor	0,5
Constant Current	Yes
500mA	6-12V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Eaglerise
Brand	Eaglerise
Brand Illumination Data	Eaglerise
Illumination Data	
Illumination Data Colour Temperature	3000K
Illumination Data	
Illumination Data Colour Temperature	3000K
Illumination Data Colour Temperature Lumen Output	3000K 330lm
Illumination Data Colour Temperature Lumen Output Light Efficiency	3000K 330lm 55lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3000K 330lm 55lm/W
Illumination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3000K 330lm 55lm/VV 80 270°
Illumination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3000K 330lm 55lm/VV 80 270°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3000K 330lm 55lm/VV 80 270°
Illumination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3000K 330lm 55lm/W 80 270°
Illumination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	3000K 330lm 55lm/W 80 270°

Box Weight	0.772kg
Pcs/Carton	18
Barcode	5291889058199
HS Code	9405409900

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes



