

20 Garden & Underwater > LED Garden Path Lights Aluminium

67460B/AN/W



2x6W LED Bollard, IP54 for Garden illumination.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	20 Garden & Underwater
Family	LED Garden Path Lights Aluminium
Order Code	67460B/AN/W
Colour	Anthracite
Material	Aluminium
Diffuser Material	PC
Shape	Rectangular
Length	100mm
Width	50mm
Height	600mm
Surface Floor/Ground	Yes
Outdoor	Yes

Adjustable	No
IK Rating	10



No
10

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x6W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	

100-240V
Yes
Yes

2x6W
IP54
LED built in
No


Fitting


Input Type	Constant Current
Input Current	300mA
Voltage	38V
Power(Watts)	11,2W
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835

Constant Current
300mA
38V
11,2W
IP54
LED built in
SMD 2835


Gear

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes

Led Driver
100-240V
Yes
Yes

Power(Watts)	9-12W
Power Factor	0,9
Constant Current	Yes
300mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	55°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
Protection	Short Circuit

Illumination Data

Colour Temperature	3000K
Lumen Output	2x500lm
Light Efficiency	83,33lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	2.700kg
Pcs/Carton	4
Barcode	5291889059738
HS Code	9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

