

Product Datasheet

www.1-light.eu

19 Wall Recessed & Inground>Ground Surface Mounted Range Die cast

69058C/G/W



4x3W COB LED Surface ground, IP67 for path illumination.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
IES O CE	200mm - 42mm -

Gallery



Physical Specification

Item Group

19 Wall Recessed & Inground

		••	
	\mathbf{n}		\ /
- a	m		v
			y

Ground Surface Mounted Range Die cast

Order Code	69058C/G/W
Colour	Grey
Material	Die Cast
Shape	Circular
Height	42mm



Diameter	200mm
Surface Floor/Ground	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	10

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	4x3W
IP Rating	IP67
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	33V

Power(Watts)	4x2,5W
IP Rating	IP67
Light Source	LED built in
LED Type	СОВ
LED Brand	Edison



Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	9-12W
Power Factor	0,9
Constant Current	Yes
300mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise

Illumination Data

Colour Temperature	3000K
Lumen Output	600lm
Light Efficiency	50lm/W
CRI	80
Illumination Diagram	

Box Weight	0.858kg
Pcs/Carton	12
Barcode	5291889065845
HS Code	9405413990



Warranty

2 years

switch to one light!



