

08 Strips & Profiles > The 4,8W/m Indoor 24V

## 7820/D



Flexible LED light strip, with SMD2216 LEDs, 70LEDs/meter, 4,8W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 10cm (7-LED segment).

Requires 24V DC constant voltage LED driver.


Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions




### Gallery



### Accessories



7822



7824

Related items



20030

Physical Specification


Item Group	08 Strips & Profiles
Family	The 4,8W/m Indoor 24V
Order Code	7820/D
Shape	Rectangular
Length	5000mm
Width	8mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

Electrical Characteristics

Fitting

Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	III
Power(Watts)	4,8W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2216
LED Brand	Refond
LED Number	70LEDs/m

## Illumination Data

Colour Temperature	6000K
Lumen Output	490lm/m
Light Efficiency	102,08lm/W
CRI	90
Illumination Diagram	

## Packing Info

Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Box Weight	0,17kg
Pcs/Carton	40
Barcode	5291889017660
HS Code	9405409989

## Energy Label



Energy Class	E
--------------	---

Warranty

5 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

