

08 Strips & Profiles > The Ultra Slim Range 24V

## 7823/C



Slim Flexible LED light strip, with SMD2216 LEDs, 140LEDs/meter, 9,6W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 5cm (7-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.




### Downloads



### Dimensions



### Gallery



### Related items



20030

### Physical Specification


Item Group

08 Strips & Profiles


Family	The Ultra Slim Range 24V
Order Code	7823/C
Shape	Rectangular
Length	5m
Width	5mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes

## Electrical Characteristics

### Fitting

Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	9,6W/m
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2216
LED Brand	Refond
LED Number	140Leds/m

## Illumination Data

Colour Temperature	4000K
Lumen Output	970lm/m
Light Efficiency	101.04lm/W
CRI	90
Illumination Diagram	

## Packing Info

Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Box Weight	0,18kg
Pcs/Carton	40
Barcode	5291889048770
HS Code	9405409989

## Certification & Warranty

Warranty	5 Years
Weee Directive	Yes

switch to  
**one light!**

one  
LIGHT

